

SPEC OIL OUTBOARD OIL

DESCRIPTION

Spec Oil outboard is a premium performance, two stroke, and marine outboard motor oil formulated with special additives. Spec Oil outboard is pre-diluted with a high flash point solvent to facilitate mixing with petrol at all temperatures. Spec Oil outboard is designed for engines requiring NMMA TC W3 lubricants.

APPLICATION

All water cooled, two stroke, marine outboard engines, oil injected engines and air cooled two stroke engines where API TD or NMMA oils are specified.

PERFORMANCE STANDARD

- Formulated to meet NMMA (National Marine Manufacturers Association) TC W3
- API TD
- NMMA TC-W2

BENEFITS

Spec Oil outboard is specially blended with virgin refined mineral oil and ashless additive to maintain a high power output. This oil provides piston cleanliness and protection against ring sticking and power loss by maintaining combustion efficiency. The special ashless additive enhances lubricity as well as coating surfaces with a tough lubricant to protect against wear under peak performance conditions, reduces spark plug fouling and ensures that ash induces deposits are not formed in the combustion chamber.

KEY PROPERTIES

Viscosity @ 40 °C	42 Cst
Flash Point °C	90
Ash, m %	0.01
Viscosity Index (Min)	130
Pour Point °C (Max)	-30
Colour Visual	Blue/green